

## MGM INSTITUTE OF HEALTH SCIENCES CENTRAL PURCHASE DEPARTMENT (CPD)

Plot 1 & 2, Sector -1 Kamothe, Navi Mumbai - 410209

## eTender for Opthal Equipment

Tenders invited from reputed Manufactures of **Opthal Equipment** for supply and installation at MGM, SBS, Kamothe, Navi Mumbai. in the format given below:

Name & Address of Vendor:		

Sr. No.	Name of Item with Specifications	Qty.	Make (Offered)	Model (Offered)	Rate per Unit (Excluding GST)	GST %
	Phoropter					
1	The range of sphere powers can be specified in diopters (\(D\)) The step size between sphere powers can be specified in diopters (\(D\)) The distance of the optical center, also known as the pupil distance (\(PD\)), can be specified in millimeters (\(mm\)) The step size between pupil distances can be specified in millimeters (\(mm\)) The cylinder axis can be specified in degrees (\(\degree \)) The prism power can be specified in prism diopters (\(prism diopters \)) The cross cylinder power can be specified in diopters (\(D\)) The field of view can be specified in millimeters (\(mm\)) The head-support adjustment can be specified in millimeters (\(mm\))	1 No				
2	Refraction chair unit with surgeon stool  Seat height- 550 mm to 710mm  Net weight-196Kg  Sliding table loaded weight-25Kg (max 2 equipment's  Sliding table top size-790 X 400mm  Trial lens set tray size-555 X 345 X 10mm  Prescription table size-400 X 410mm  Motor-24VDC  Minimum area required-8'x 10' for erect position  Power supply for auxiliary equipments-3,4, 6,12v,& 230 V (4 Sockets)  Standard colors available-Blue, Grey, Maroon, Green, Black	1 No				

Sr. No.	Name of Item with Specifications	Qty.	Make (Offered)	Model (Offered)	Rate per Unit (Excluding GST)	GST %
	Digital Eyechart					
	Medical standard LED screen.					
	Free upgrade through WIFI all life time.					
	Hardware and system are entirely integrated.					
3	Work out of the box, plug and play.	1 No				
	Full-function and multiple charts.					
	RF wireless remote, fluorescent keypad.					
	Florescent keypad, testing in dark room is much easier.					
	No aiming!					
	Digital Lensometer					
	TypeDirect scale reading system					
	TargetCorona Target					
	Vertex Power Scale0 TO+_ Diopters					
	Graduations0.25D Graductions Upto +_20D					
	Prism Diopter ScaleOTO 5 Prism DIOPTER, 1Graduation					
4	Protractor Scale0 _180_0 5 Gradution on main Scale	1 No				
	Holding Capacity30mm to 80mm Diameter Lenses					
	Tilt Angle0 to 90 Adjustable					
	Dimension300(L)x? 150(W)x 200(H)mm					
	Weight2.5Kg.{Appx.)					
	Power Source2xl.5VAA Size Dry Cel I(or) 220 Volt AC SUPPLY					
	ILLumination2.3 Volt					
Kind	lly email your lowest quotations for above items with detailed specific	cations, terms and co	onditions as wel	l as applicable	Brochure / Catlog, (	Client l
with	n installation Year and their Contact numbers to etenders@mgmuhs.o	com only.				

Date:	Signature of Tenderer:
	Name:
	Designation:
	Email ID:
Seal	Mobile No.:
	Full Address: